



1/5




**Fig. 1**



**Fig. 2**

10054354 48245001




**Fig. 3**

52 63 64 50 53  
 ner sufficiently  
 by a person skilled i  
 art" for this purpose  
 ctitioner aware not o  
 , itself and the refere  
 mmon general know  
 e application. He is a  
 and the c

51 54 61  
 on skilled in the art  
 purpose is consid  
 are not only of the t  
 e references therein  
 al knowledge in the  
 e is assumed to ha  
 the capacity for

60 62

**Fig. 8**



**Fig. 7a**

**Fig. 7b**




Fig. 6




Fig 4 a




Fig 4 b




Fig. 5


100543304-1226007

4/5

ner sufficiently  
by a person skilled i  
art" for this purpose  
etitioner aware not o  
, itself and the reforc  
mmon general know  
e application. He is a  
and the c

15  
32  
33  
37

**Fig. 9**



**Fig. 10**

10054294.4

5/5

US-5,301,243 discloses a hand-held scanner for reading characters from a string of characters on a substrate. The scanner is moved in contact with the substrate along the character line and has an optical system which images a small part of the substrate. The optical system comprises a CCD type line sensor provided with a plurality of light-sensitive elements arranged in a line. When the scanner is passed across the characters on the substrate, a succession of vertical slices of the characters and of the spaces between them is recorded.

Fig 11a




Fig. 11b



Fig 11c

29

10054234-1100